

Heavy-duty HVP 88430



Application

Heavy-duty concealed beam connector for wood-wood connections.

Product Specifications

Dimensions w x h x d	120 x 300 x 20
Number of screws	24
Screw size	ø 8 x 100 – 200
Minimum timber section with screw ø 8 x 160 (mm) header	160 x 320
Joist	140 x 320
Characteristic load capacity* ø 8 x 160	100.58
ø 8 x 200	124.42
Carton quantity	4
CE	*

* F_{2,Rk} (kN) for GL24h with fully threaded screws: ø 8 x 160 with effective thread length of 150 mm and ø 8 x 200 with effective thread length of 190 mm. For other screws and thread lengths or wood based materials: cf. design manual.

Product Description

Main and secondary beam connection wood to wood

Main and secondary beam connection wood to wood with PITZL HVP 88430.1000 according to ETA-15/0187. The connection to secondary beam with 12 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. Connection to main beam with 12 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. The lift-off protection with 2 pcs. SFS HT cylinder head screws with a diameter of 6.0 mm and a length of 20 mm is required. A transverse tension lock is/is not to be provided in the area of the main/secondary beam. The main beam is/is not torsional fixed or sufficiently held. The serviceability has to be proven by the stiffness characteristics. A fire resistance time of 60 minutes is to be solved by appropriate design measures.

The characteristic load bearing capacity according to timber strength class C24 are:

F_{1,Rk} = 48.32 / 54.09 / 59.78 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 93.19 / 104.30 / 115.29 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 38.73 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 1555.45 kN – Rotation moment in the axis of the secondary beam

The characteristic load bearing capacity according to timber strength class GL24h are:

F_{1,Rk} = 52.15 / 58.37 / 60.00 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 100.58 / 112.57 / 124.42 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 40.62 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 1631.37 kN – Rotation moment in the axis of the secondary beam

The number and arrangement of the connectors as well as the installation and assembly must be taken from the specifications in accordance with ETA-15/0187. Basically, the requirements of DIN EN 1995 must be fulfilled.

Heavy-duty HVP 88430

Static Values

Effective thread length (l_{ef})		Minimal section (mm)		Characteristic load capacity R_k (KN)							
				Solid wood C24 ($\rho_k = 350 \text{ kg/m}^3$)				Glued-laminated timber GL24h ($\rho_k = 385 \text{ kg/m}^3$)			
Screws	l_{ef} (mm)	H	J	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$
$\varnothing 8 \times 160$	150	160 x 320	140 x 320	93.19	36.40	38.73	48.32	99.53	36.40	40.35	51.61
$\varnothing 8 \times 180$	170	180 x 350	140 x 350	104.30			54.09	111.40			57.76
$\varnothing 8 \times 200$	190	200 x 380	140 x 380	115.29			59.78	123.12			60.00

(Erstellt)	(Datum)	(Werkstoff)	EN AW 6082	nach	(Maßstab)	
Autret	30.09.2014	(Beschichtung)				
Abehebesicherung	30.09.14					
Ind. Änderung	Datum					Name
(Benennung)	HVP-Schwerlast					
(Zeichnungsnummer / Artikel-Nr.)	88430.0000 Teil 1					Blatt /

(Erstellt)	(Datum)	(Werkstoff)	EN AW 6082	nach	(Maßstab)	
Autret	03.06.2014	(Beschichtung)				
Ind. Änderung	Datum	Name				
(Benennung)	HVP-Schwerlast					
(Zeichnungsnummer / Artikel-Nr.)	88430.0000 Teil 2					Blatt /