

Heavy-duty HVP 88450



Product Specifications

Dimensions w x h x d	120 x 500 x 20
Number of screws	40
Screw size	ø 8 x 100 – 200
Minimum timber section with screw ø 8 x 160 (mm) header	170 x 520
Joist	140 x 520
Characteristic load capacity* ø 8 x 160	201.15
ø 8 x 200	248.84
Carton quantity	4
CE	*

Application

Heavy-duty concealed beam connector for wood-wood connections.

* F_{2,Rk} (kN) for GL24h with fully threaded screws: ø 8 x 160 with effective thread length of 150 mm and ø 8 x 200 with effective thread length of 190 mm. For other screws and thread lengths or wood based materials: cf. design manual.

Product Description

Main and secondary beam connection wood to wood

Main and secondary beam connection wood to wood with PITZL HVP 88450.1000 according to ETA-15/0187. The connection to secondary beam with 20 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. Connection to main beam with 20 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. The lift-off protection with 2 pcs. SFS HT cylinder head screws with a diameter of 6.0 mm and a length of 20 mm is required. A transverse tension lock is/is not to be provided in the area of the main/secondary beam. The main beam is/is not torsional fixed or sufficiently held. The serviceability has to be proven by the stiffness characteristics. A fire resistance time of 60 minutes is to be solved by appropriate design measures.

The characteristic load bearing capacity according to timber strength class C24 are:

F_{1,Rk} = 48.32 / 54.09 / 59.78 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 186.38 / 208.61 / 230.57 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 64.54 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 4782.54 kN – Rotation moment in the axis of the secondary beam

The characteristic load bearing capacity according to timber strength class GL24h are:

F_{1,Rk} = 52.15 / 58.37 / 64.52 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 201.15 / 225.14 / 248.84 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 67.69 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 5015.97 kN – Rotation moment in the axis of the secondary beam

The number and arrangement of the connectors as well as the installation and assembly must be taken from the specifications in accordance with ETA-15/0187. Basically, the requirements of DIN EN 1995 must be fulfilled.

Heavy-duty HVP 88450

Static Values

Effective thread length (l_{ef})		Minimal section (mm)		Characteristic load capacity R_k (KN)							
				Solid wood C24 ($\rho_k = 350 \text{ kg/m}^3$)				Glued-laminated timber GL24h ($\rho_k = 385 \text{ kg/m}^3$)			
Screws	l_{ef} (mm)	H	J	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$
$\varnothing 8 \times 160$	150	170 x 520	140 x 520	186.38	36.40	64.54	48.32	199.06	36.40	67.25	51.61
$\varnothing 8 \times 180$	170	190 x 550	140 x 550	208.61			54.09	222.79			57.76
$\varnothing 8 \times 200$	190	210 x 580	140 x 580	230.57			59.78	246.25			63.85

(Erstellt) Autret	(Datum) 30.09.2014	(Werkstoff) EN AW 6082 (Beschichtung)	nach	(Maßstab)			
Abhebesicherung	30.09.14						
Ind. Änderung	Datum				Name		
(Benennung)	HVP-Schwerlast				(Zeichnungsnummer / Artikel-Nr.)	88450.0000 Teil 1	
					Blatt	/	

(Erstellt) Autret	(Datum) 03.06.2014	(Werkstoff) EN AW 6082 (Beschichtung)	nach	(Maßstab)			
Abhebesicherung							
Ind. Änderung	Datum				Name		
(Benennung)	HVP-Schwerlast				(Zeichnungsnummer / Artikel-Nr.)	88450.0000 Teil 2	
					Blatt	/	