

HVP 88550



Application

Heavy-duty concealed beam connector for wood-wood connections. The width of 140 mm is optimally suitable for wide beams (from 170 mm) under very high loads.

Product Specifications

Dimensions w x h x d	140 x 500 x 20
Number of screws	52
Screw size	ø 8 x 100 – 200
Minimum timber section with screw ø 8 x 160 (mm) header	170 x 520
Joist	170 x 520
Characteristic load capacity* ø 8 x 160	276.58
ø 8 x 200	342.15
Carton quantity	4
CE	*

* F_{2,Rk} (kN) for GL24h with fully threaded screws: ø 8 x 160 with effective thread length of 150 mm and ø 8 x 200 with effective thread length of 190 mm. For other screws and thread lengths or wood based materials: cf. design manual. Screws up to 200 mm length and the expanded heavy-duty series 885 enable a high augmentation of the load capacity.

Product Description

Main and secondary beam connection wood to wood

Main and secondary beam connection wood to wood with PITZL HVP 88550.1000 according to ETA-15/0187. The connection to secondary beam with 26 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. Connection to main beam with 26 SFS HT (Heco) screws with a diameter of 8.0 mm and a length of 160/180/200 mm. The lift-off protection with 2 pcs. SFS HT cylinder head screws with a diameter of 6.0 mm and a length of 20 mm is required. A transverse tension lock is/is not to be provided in the area of the main/secondary beam. The main beam is/is not torsional fixed or sufficiently held. The serviceability has to be proven by the stiffness characteristics. A fire resistance time of 60 minutes is to be solved by appropriate design measures.

The characteristic load bearing capacity according to timber strength class C24 are:

F_{1,Rk} = 48.32 / 54.09 / 59.78 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 256.28 / 286.83 / 317.03 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 83.90 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 5737.76 kN – Rotation moment in the axis of the secondary beam

The characteristic load bearing capacity according to timber strength class GL24h are:

F_{1,Rk} = 52.15 / 58.37 / 64.52 kN – Force acting in direction of the secondary beam
 F_{2,Rk} = 276.58 / 309.56 / 342.15 kN – Force acting in direction of insertion
 F_{3,Rk} = 36.40 kN – Force acting against direction of insertion
 F_{4,Rk} = 88.00 kN – Force acting perpendicular to direction of insertion
 M_{tor,J,Rk} = 6017.81 kN – Rotation moment in the axis of the secondary beam

The number and arrangement of the connectors as well as the installation and assembly must be taken from the specifications in accordance with ETA-15/0187. Basically, the requirements of DIN EN 1995 must be fulfilled.

HVP 88550

Static Values

Effective thread length (l_{ef})		Minimal section (mm)		Characteristic load capacity R_k (KN)							
				Solid wood C24 ($\rho_k = 350 \text{ kg/m}^3$)				Glued-laminated timber GL24h ($\rho_k = 385 \text{ kg/m}^3$)			
Screws	l_{ef} (mm)	H	J	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$	$F_{2,RK}$	$F_{3,RK}$	$F_{4,RK}$	$F_{1,RK}$
$\varnothing 8 \times 160$	150	170 x 520	170 x 520	256.28	36.40	83.90	48.32	273.70	36.40	87.43	51.61
$\varnothing 8 \times 180$	170	190 x 550	170 x 550	286.83			54.09	306.34			57.76
$\varnothing 8 \times 200$	190	210 x 580	170 x 580	317.03			59.78	338.59			63.85

(Erstellt) Autret	(Datum) 30.09.2014	(Werkstoff) EN AW 6082	nach	(Maßstab)
Abhebesch.		30.09.14		
		 Pitzl [®] Metallbau Holzverbindungen Pfostenträger		
Ind.	Änderung			
(Benennung) HVP-Schwerlast		(Zeichnungsnummer / Artikel-Nr.) 88550.0000 Teil 1		Blatt /

(Erstellt) Autret	(Datum) 03.06.2014	(Werkstoff) EN AW 6082	nach	(Maßstab)
		30.09.14		
		 Pitzl [®] Metallbau Holzverbindungen Pfostenträger		
Ind.	Änderung			
(Benennung) HVP-Schwerlast		(Zeichnungsnummer / Artikel-Nr.) 88550.0000 Teil 2		Blatt /