

Daily – quick clean

Ready to go in only 3 minutes.

A quick daily cleaning is recommended if the tool is heavily used or painted rivets are being installed. Follow these easy steps:

1. Remove the battery from the tool.



2. Unscrew the head using a 14mm, 24mm or adjustable flat wrench. Sometimes a 27mm wrench may be required depending on tool.



3. Remove the deposits and dirt in the head.



Note: If using a BULB-TITE® nosepiece, a 12mm wrench is required.

Tool warranty

All GESIPA® rivet tools purchased after May 1, 2013 come with a 24-month warranty, 12 months for batteries. In each case, the conditions set forth in the instruction manual shall apply (proof by invoice or delivery note required).

Damages resulting from natural wear and tear, overloading, use of unsuitable batteries or inexperienced handling will be excluded from the warranty. Damages resulting from material or manufacturing faults will be repaired or replaced free of charge. Claims can only be accepted if the complete riveting tool is returned to the distributor of GESIPA®.

4. Clean the nose tip from deposits and sparingly lubricate or grease.



5. Re-attach the nose and the tool is ready to go!



Weekly maintenance

A weekly cleaning of the tool is recommended if it is heavily used or painted rivets are being installed.

1. Remove the battery from the tool.



2. Unscrew the head using a 14mm, 24mm or adjustable flat wrench. Sometimes a 27mm wrench may be required depending on tool.



3. Remove the deposits and dirt in the head.



4. Open the jaw mechanism with two wrenches: PowerBird® Pro & AccuBird® Pro – use 2 x 17mm wrenches; PowerBird® & Accubird® – use a 14mm and 17mm wrench.



5. Take the jaw out (3 pieces) and clean them with a brush.



6. Replace rusty or blunt jaws with new ones.



7. Grease the inside of the jaw housing. Put jaws back in place and re-assemble mechanism with two wrenches.



8. Clean the front of nose piece.



9. Re-attach the head to the tool.

Quick checks

Tool not working? Try the following quick checks:



Battery OK?



Is the head dirty?



Nose piece worn?



Jaw mechanism tight?



Correct nose piece?



Jaws blunt?



GESIPA® Rivet Guns

Maintenance & quick help guidelines

AccuBird® Pro



PowerBird® Pro



AccuBird®



PowerBird®



Scan the QR tags for videos



Get started & maintenance of tool



Quick help
Rivet is not set



Quick help
Mandrel not ejected



Quick help
Red light is on

US
T 800 234 4533
www.sfsintecusa.com

Canada
T 866 847 5400
www.sfsintec.ca

This guideline will help you maintain your rivet gun to ensure proper performance over the life of the tool. Regular maintenance will extend the service life of your high-quality GESIPA® tool.